

VRLA/SLA Battery series is designed with AGM Long Life / Duration In High Performance Plate with Gain Extra Powder in Purify Electrolyte. Innovation Design of Fully Maintenance Free in Float Life 12 years. This is Highly Suited to Backup Applications in UPS/ EPS, Security Alarm System, Emergency Light, Telecommunication System and other

Feature

- Smart UPS Battery Design up to 10%
- Battery Capacity 100Ah / 1700W-15min
- AGM/SLA -Seal Lead Acid Battery
- Maintenance Free Battery Operation
- Non-Spillable Construction Design
- ABS Container & Cover UL94HB-0
- Safety Valve in explosion proof
- CE & UL Product Certificate
- ISO9001 & ISO14001 Certified Factory

Application

- UPS & EPS
- Emergency System
- Communication Eq.
- Security System
- Control Equipment
- Alarm System
- Medical Equipment
- Cable TV & CCTV


Specifications

Voltage Normal : 12 VDC in 6 Cell
Capacity @20Hr : 106Ah @5.29A/64W
 @ 5Hr : 84Ah @16.9A/194W
 @ 1Hr : 62Ah @61.8A/690W
 @15min : 39Ah @155A/1704W (*UPS)
 @ 5min : 22Ah @266A/2856W (*UPS)
Max. Discharge : 1400A @14C
Max. Charge Current : 30A @0.3C
Internal Resistance : Apporx. 5 mΩ Full Charge at 25°C
Design Float Life : 12 years at 25 °C
Cycle Lift Service : 1500 cycles at DOD 25%
Float Charge Voltage : 14.4-15.0V (-30mV/°C) at 25°C
Cycle Charge Voltage : 13.5-13.8V (-20mV/°C) at 25°C
Operation Temp. : Normal 25+/-3 °C
 : Discharge -15 - 50 °C
 : Charge -15 - 50 °C
 : Storage -15 - 50 °C
Self Discharge : more than 6 Month at 25°C
Terminal : M6
Container Material : ABS UL94 HB-0 (Option :UL94V-0)
Physical : 330x171x214mm – 30 Kgs


EX12100-1700W : 12V-100Ah /1700W-15min




Dimension 330x171x214mm Weight = 30kgs @ M6




Terminal Voltage (V) and Discharge Time




Battery Voltage and Charge Time for Standby Use



Battery Voltage and Charge Time for Cycle Use



Cycle Service Life



Constant Current (Amp) and Power (Watt/Box) Discharge Table

VRLA-Battery Performance : %DOD , Constant Current , Constant Power (25°C/ 10.5 F.V.)

	5 Min	10 Min	15 Min	20 Min	30 Min	60 Min	2 Hr	3 Hr	5 Hr	10 Hr	20 Hr
Capacity Batt.	22.2Ah	32.5Ah	38.8Ah	42Ah	49Ah	61.8Ah	70Ah	81Ah	84.5Ah	100Ah	106Ah
% DOD	22%	32%	39%	42%	49%	62%	70%	81%	84%	100%	106%
Cons.Current	266A	195A	155A	126A	98A	61.8A	35A	27A	16.9A	10.0A	5.29A
Cons. Power	2856W	2148W	1704W	1386W	1104W	690W	402W	310W	194W	120W	64W

Chuphotic EX12100-1700W Rev.1.00